



SPECIFICATIONS: ASTM A615-GRADE 60
 ROUND BAR: CARBON EQUIVALENT-.45% MAX.
 YIELD STRENGTH-60 KSI MIN
 TENSILE STRENGTH-90 KSI
 ELONGATION-8"-18% MIN.
 REDUCTION AREA- 30% MIN. (1/2" TO 2")
 REDUCTION AREA- 22% MIN. (>2" TO 2 1/2")
 REDUCTION AREA- 20% MIN. (>2 1/2" TO 3")

GALVANIZE: ASTM-A153, CLASS C
 NUTS: ASTM A563-GR DH, ANSI B18.2.2

THREADS: UNIFIED NATIONAL COARSE
 ANSI B1.1 CLASS 2A
 THREADS ARE ROLLED OR CUT.

WASHERS: ASTM F-436

				REBAR- STRAIGHT THREADED BOTH ENDS GRADE 60		
				REVISION: A	P.O. COMPANY:	DRAWN BY: JEP
				DATE:	P.O. NUMBER:	CHECKED BY: AJS
				CONTRACTOR:		
				J. H. Botts LLC		
				DWG. NO.		
A	FOR RELEASE					
REV #	DESCRIPTION	DATE	BY			
	REVISIONS					