



SPECIFICATIONS: ASTM A615—GRADE 60
 ROUND BAR: CARBON EQUIVALENT—.45% MAX.
 YIELD STRENGTH—60 KSI MIN
 TENSILE STRENGTH—90 KSI
 ELONGATION—8"—18% MIN.
 REDUCTION AREA— 30% MIN. (1/2" TO 2")
 REDUCTION AREA— 22% MIN. (>2" TO 2 1/2")
 REDUCTION AREA— 20% MIN. (>2 1/2" TO 3")

GALVANIZE: ASTM—A153, CLASS C

NUTS: ASTM A563—GR DH, ANSI B18.2.2

THREADS: UNIFIED NATIONAL COARSE
 ANSI B1.1 CLASS 2A
 THREADS ARE ROLLED OR CUT.

WASHERS: ASTM F—436

				REBAR— STRAIGHT THREADED ONE END GR 60		
				REVISION: A	P.O. COMPANY:	DRAWN BY: JEP
				DATE:	P.O. NUMBER:	CHECKED BY: AJS
				CONTRACTOR:		
				J. H. Botts LLC		
				DWG. NO.		
A	FOR RELEASE					
REV #	DESCRIPTION	DATE	BY			
	REVISIONS					
				1 of 1		